



XJ-V110W

CORE SERIES

LampFree. MercuryFree. StressFree.
The Casio CORE Series incorporates essential features with Casio's Industry Leading LampFree® Technology to create a budget friendly LampFree® projector. The CORE Series is available in XGA and WXGA resolutions and up to 3500 ANSI lumen brightness utilizing a 1.5x manual zoom lease.

Compact and lightweight, the CORE Series delivers reliable long term operation, exceptional image quality & connectivity and is ideal for use in classrooms, in the boardroom or on the road. Reliable and built to last, the CORE Series is covered by a 3-year parts and labor warranty plus a 5 year/10,000 hour light source warranty.

Key Features

- HDMI input
- Dust Resistant design
- Instant Light Control 7 level
- 1.5 X Manual Zoom/Focus Lens
- DLP® Technology

LampFree Features

- · Laser & LED Light Source
- Long Life, 20,000 hour estimated operating life
- · No Lamp replacement required
- No Down Time
- Low Power Consumption
- Mercury Free
- Instant On (5 seconds to full brightness)
- Instant Off no cool down required

Terminal Interface



CASIO Projector Specifications	CORE SERIES XJ-V110W
	WXGA
Native Resolution	1280 x800
Native Aspect Ratio	16:10
	3500 lumens
Brightness	
Display Device	0.65 -inch DLP® chip
Contrast Ratio	20000:1
ens Type	1.5X Manual Zoom & Focus
ens Offset	33%
ight Source	Laser & LED Hybrid
Estimated Light Source Life	Up to 20,000 hours
Projection Screen Size (Min-Max)	35 to 300-inch diagonal
Projection Range	_
60-inch screen	5.4-7.9 ft
100-inch screen	9.2-13.5 ft
Minimum Throw Distance	3.0 ft
Throw Ratio	1.32-1.93:1
(eystone Correction	Vertical +30° (Auto) Vertical + or - 30° (Manual)
	Full color (up to 1.07 billion colors)
Color Reproduction	
ower Source	AC 100 ~240V, 50/60 Hz
ower Consumption	_
	190 W light control "off" Bright selected
Operating	155 W light control "on" and "Light Output 7" Selected
Standby	0.12 W
ERMINAL CONNECTIVITY	
/ideo Signal Compatibility	_
Video Systems	No
DTV/HDTV	480i/480p/576i/576p/720p/1080i/1080p
Maximum Computer Input	WUXGA (1920 x 1200) *Reduced blanking signal
NPUTS	
NPUIS	
RGB/Component Video Input	mini D-Sub 15 pin x 1 (Also use as YCbCr/YPbPr input—
(ab) component video input	commercially available adapter required)
HDMI	HDMI Type A x 1, HDCP and audio support
Composite Video	No
Audio	3.5mm stereo mini jack x 1
Aicrophone	No
JSB	No
	No
Built-in Memory	· · · · · · · · · · · · · · · · · · ·
.ogo Transfer	No
Wireless Capability	No
DUTPUTS	
	25 con Maria Cross Mariable A. Pr
Audio	3.5 mm Mini - Stereo, Variable Audio
RGB Output	No
AUDIO AND CONTROL SYSTEMS	
Audio system	No
Control Terminal	
	PS-222C (D sub 9 pip) v 1 Cross Cable (Null Modern) required
RS-232	RS-232C (D sub 9 pin) x 1, Cross Cable (Null Modem) required
RS-232 LAN	No
RS-232 LAN	
RS-232 LAN Control System Compatibility	No
RS-232 LAN Control System Compatibility DTHER INFORMATION	No
RS-232 LAN Control System Compatibility DTHER INFORMATION Jsage Environment	No No
RS-232 LAN Control System Compatibility DTHER INFORMATION	No
RS-232 LAN Control System Compatibility DTHER INFORMATION Jsage Environment Operating Temp/Humidity	No No — 41-95°F/20-80% (non condensation)
RS-232 LAN Control System Compatibility DTHER INFORMATION Usage Environment Operating Temp/Humidity High Altitude Mode	No No — 41-95°F/20-80% (non condensation) Yes (for operation 5,000-10,000 ft)
RS-232 LAN Control System Compatibility DTHER INFORMATION Usage Environment Operating Temp/Humidity High Altitude Mode Extended operation (24 x 7)	No No 41-95°F/20-80% (non condensation) Yes (for operation 5,000-10,000 ft) Yes – Note: Projector must be turned off once every 24 hours
RS-232 LAN Control System Compatibility DTHER INFORMATION Jsage Environment Operating Temp/Humidity High Altitude Mode Extended operation (24 x 7)	No No No H-95°F/20-80% (non condensation) Yes (for operation 5,000-10,000 ft) Yes – Note: Projector must be turned off once every 24 hours Free orientation
RS-232 LAN Control System Compatibility DTHER INFORMATION Usage Environment Operating Temp/Humidity High Altitude Mode Extended operation (24 x 7) Rotation Projection	No No 41-95°F/20-80% (non condensation) Yes (for operation 5,000-10,000 ft) Yes – Note: Projector must be turned off once every 24 hours
RS-232 LAN Control System Compatibility DTHER INFORMATION Usage Environment Operating Temp/Humidity High Altitude Mode Extended operation (24 x 7) totation Projection temote Control Range	No No No No H-95°F/20~80% (non condensation) Yes (for operation 5,000~10,000 ft) Yes – Note: Projector must be turned off once every 24 hours Free orientation 16.4 ft Maximum
RS-232 LAN Control System Compatibility DTHER INFORMATION Usage Environment Operating Temp/Humidity High Altitude Mode extended operation (24 x 7) totation Projection Remote Control Range eiecurity Compatibility	No No No No No H1-95°F/20-80% (non condensation) Yes (for operation 5,000-10,000 ft) Yes – Note: Projector must be turned off once every 24 hours Free orientation 16.4 ft Maximum Kensington™ Compatible/Power On Password
RS-232 LAN Control System Compatibility DTHER INFORMATION Usage Environment Operating Temp/Humidity High Altitude Mode Extended operation (24 x 7) Lotation Projection Lemote Control Range ecurity Compatibility Leiling Mountable	No No No No No No No No A1-95°F/20-80% (non condensation) Yes (for operation 5,000-10,000 ft) Yes – Note: Projector must be turned off once every 24 hours Free orientation 16.4 ft Maximum Kensington™ Compatible/Power On Password Yes, available and sold separately by 3rd party vendors
RS-232 LAN Control System Compatibility DTHER INFORMATION Usage Environment Operating Temp/Humidity High Altitude Mode Extended operation (24 x 7) Lotation Projection Lemote Control Range ecurity Compatibility Leiling Mountable	No No No No No No No A1-95°F/20-80% (non condensation) Yes (for operation 5,000-10,000 ft) Yes – Note: Projector must be turned off once every 24 hours Free orientation 16.4 ft Maximum Kensington™ Compatible/Power On Password Yes, available and sold separately by 3rd party vendors M4 x 4 (not included) Insert depth (5-8 mm)
RS-232 LAN Control System Compatibility DTHER INFORMATION Usage Environment Operating Temp/Humidity High Altitude Mode Extended operation (24 x 7) Rotation Projection Remote Control Range iecurity Compatibility Ceiling Mountable Leiling Mount Screws	No H1-95°F/20-80% (non condensation) Yes (for operation 5,000-10,000 ft) Yes – Note: Projector must be turned off once every 24 hours Free orientation 16.4 ft Maximum Kensington™ Compatible/Power On Password Yes, available and sold separately by 3rd party vendors M4 x 4 (not included) Insert depth (5-8 mm) 3 Years Parts & Labor plus 5 years or 10,000 hours on light source, see Warranty Stateme
RS-232 LAN Control System Compatibility DTHER INFORMATION Usage Environment Operating Temp/Humidity High Altitude Mode Extended operation (24 x 7) Rotation Projection Remote Control Range eccurity Compatibility Leiling Mountable Leiling Mount Screws Limited Warranty	No N
RS-232 LAN Control System Compatibility DTHER INFORMATION Usage Environment Operating Temp/Humidity High Altitude Mode Extended operation (24 x 7) Rotation Projection Remote Control Range recurity Compatibility Ceiling Mountable Leiling Mount Screws Limited Warranty Included Accessories	No A1-95°F/20~80% (non condensation) Yes (for operation 5,000-10,000 ft) Yes – Note: Projector must be turned off once every 24 hours Free orientation 16.4 ft Maximum Kensington™ Compatible/Power On Password Yes, available and sold separately by 3rd party vendors M4 x 4 (not included) Insert depth (5-8 mm) 3 Years Parts & Labor plus 5 years or 10,000 hours on light source, see Warranty Stateme included with product for complete details
RS-232 LAN Control System Compatibility DTHER INFORMATION Usage Environment Operating Temp/Humidity High Altitude Mode Extended operation (24 x 7) Rotation Projection Remote Control Range recurity Compatibility Ceiling Mountable Leiling Mount Screws Limited Warranty Included Accessories	No N
RS-232 LAN Control System Compatibility DTHER INFORMATION Usage Environment Operating Temp/Humidity High Altitude Mode Extended operation (24 x 7) Rotation Projection Remote Control Range security Compatibility Ceiling Mountable Ceiling Mount Screws Limited Warranty Included Accessories Included Software	No N
RS-232 LAN Control System Compatibility DTHER INFORMATION Usage Environment Operating Temp/Humidity High Altitude Mode Extended operation (24 x 7) Votation Projection Exempte Control Range Execurity Compatibility Exiling Mountable Deiling Mount Screws Limited Warranty Included Accessories Included Software Optional Accessories	No 41-95°F/20-80% (non condensation) Yes (for operation 5,000-10,000 ft) Yes – Note: Projector must be turned off once every 24 hours Free orientation 16.4 ft Maximum Kensington™ Compatible/Power On Password Yes, available and sold separately by 3rd party vendors M4 × 4 (not included) Insert depth (5-8 mm) 3 Years Parts & Labor plus 5 years or 10,000 hours on light source, see Warranty Stateme included with product for complete details Wireless Remote Control, Batteries (AAA-size.2), AC Power Cord, RGB Cable, Warranty and Safety Precautions No Soft carrying case YB-2
RS-232 LAN Control System Compatibility DTHER INFORMATION Usage Environment Operating Temp/Humidity High Altitude Mode Extended operation (24 x 7) totation Projection Remote Control Range Recurity Compatibility Leiling Mountable Ceiling Mount Screws Limited Warranty Included Accessories Included Software Optional Accessories Labinet Color	No N
RS-232 LAN Control System Compatibility DTHER INFORMATION Usage Environment Operating Temp/Humidity High Altitude Mode Extended operation (24 x 7) totation Projection temote Control Range ecurity Compatibility Leiling Mountable Ceiling Mount Screws Leimited Warranty Included Accessories Included Software Optional Accessories Labinet Color	No 41-95°F/20-80% (non condensation) Yes (for operation 5,000-10,000 ft) Yes – Note: Projector must be turned off once every 24 hours Free orientation 16.4 ft Maximum Kensington™ Compatible/Power On Password Yes, available and sold separately by 3rd party vendors M4 × 4 (not included) Insert depth (5-8 mm) 3 Years Parts & Labor plus 5 years or 10,000 hours on light source, see Warranty Stateme included with product for complete details Wireless Remote Control, Batteries (AAA-size.2), AC Power Cord, RGB Cable, Warranty and Safety Precautions No Soft carrying case YB-2
RS-232 LAN Control System Compatibility DTHER INFORMATION Usage Environment Operating Temp/Humidity High Altitude Mode Extended operation (24 x 7) Intotation Projection Itemate Control Range ecurity Compatibility Ceiling Mountable Leiling Mount Screws Imited Warranty Included Accessories Included Software Optional Accessories Labinet Color Immension (W x D x H)	No N
RS-232 LAN Control System Compatibility DTHER INFORMATION Usage Environment Operating Temp/Humidity High Altitude Mode Extended operation (24 x 7) totation Projection tempote Control Range ecurity Compatibility Leiling Mountable Leiling Mount Screws Imited Warranty Included Accessories Included Software Optional Accessories Labinet Color Dimension (W x D x H) Including Projections	No N
RS-232 LAN Control System Compatibility DTHER INFORMATION Usage Environment Operating Temp/Humidity High Altitude Mode Extended operation (24 x 7) Lotation Projection Lemote Control Range Lecurity Compatibility Leiling Mountable Leiling Mount Screws Leiling Mount Screws Leiling Accessories Lotation Software Lotation Color Lotation (W x D x H) Including Projections Excluding Projections Excluding Projections	No N
RS-232 LAN Control System Compatibility DTHER INFORMATION Usage Environment Operating Temp/Humidity High Altitude Mode Extended operation (24 x 7) Lotation Projection Lemote Control Range Lecurity Compatibility Leiling Mountable Leiling Mount Screws Leiling Mount Screws Leiling Accessories Lotation Software Lotation Color Lotation (W x D x H) Including Projections Excluding Projections Excluding Projections	No N
RS-232 LAN Control System Compatibility DTHER INFORMATION Usage Environment Operating Temp/Humidity High Altitude Mode Extended operation (24 x 7) Iotation Projection Itemate Control Range ecurity Compatibility Peiling Mountable Leiling Mount Screws Imited Warranty Included Accessories Included Software Optional Accessories Cabinet Color Including Projections Excluding Projections Veight	No N
RS-232 LAN Control System Compatibility DTHER INFORMATION Usage Environment Operating Temp/Humidity High Altitude Mode Extended operation (24 x 7) totation Projection tempote Control Range ecurity Compatibility Leiling Mountable Leiling Mountable Leiling Mount Screws Imited Warranty Included Accessories Included Software Optional Accessories Labinet Color Dimension (W x D x H) Including Projections Excluding Projections Veight Lacking Information	No 41-95°F/20-80% (non condensation) Yes (for operation 5,000-10,000 ft) Yes – Note: Projector must be turned off once every 24 hours Free orientation 16.4 ft Maximum Kensington™ Compatible/Power On Password Yes, available and sold separately by 3rd party vendors M4 × 4 (not included) Insert depth (5-8 mm) 3 Years Parts & Labor plus 5 years or 10,000 hours on light source, see Warranty Stateme included with product for complete details Wireless Remote Control, Batteries (AAA-size×2), AC Power Cord, RGB Cable, Warranty and Safety Precautions No Soft carrying case YB-2 White 11.8 x 11.8 x 3.8 inches NA 7.7lbs —
RS-232 LAN Control System Compatibility DTHER INFORMATION Usage Environment Operating Temp/Humidity High Altitude Mode Extended operation (24 x 7) Lotation Projection Leemote Control Range Leeroity Compatibility Leiling Mountable Leiling Mount Screws Leiling Mo	No N
RS-232 LAN Control System Compatibility DTHER INFORMATION Usage Environment Operating Temp/Humidity High Altitude Mode Extended operation (24 x 7) Intotation Projection Itemate Control Range ecurity Compatibility Ceiling Mountable Leiling Mount Screws Imited Warranty Included Accessories Included Software Optional Accessories Cabinet Color Including Projections Excluding Projections Veight Lacking Information Carton Dimensions Carton Weight	No N
RS-232 LAN Control System Compatibility DTHER INFORMATION Usage Environment Operating Temp/Humidity High Altitude Mode Extended operation (24 x 7) Votation Projection Remote Control Range Recurity Compatibility Ceiling Mountable Ceiling Mount Screws Limited Warranty Included Accessories Included Software Optional Accessories Cabinet Color Dimension (W x D x H) Including Projections Excluding Projections Veight Lacking Information Carton Dimensions	No N

countries. Specifications were thought to be correct at time of publication. All specifications and features are subject to change without notice. DLP, the DLP logo and the DLP medallion are trademarks of Texas Instruments. XCA is a registered trademark of International Business Machines Corporation in the United States. HDMI is a trademark or registered trademark of HDMI Licensing, LLC. Other product names or company names on this specification brochure are either trademarks or registered trademarks of their respective owners.

 $@\ 2016\ Casio\ America, Inc.\ All\ rights\ reserved.\ Casio\ is\ a\ registered\ trademark\ of\ Casio\ Computer\ Co.,\ Ltd.\ In\ the\ United\ States\ and/or\ other\ Casio\ Computer\ Co.,\ Ltd.\ In\ the\ United\ States\ and/or\ other\ Casio\ Casi$